

# SUBMITTAL DATA SHEET

14 RT (H,Y)VAHR168B41S (Consists of one (H,Y)VAHR096B41S and one (H,Y)VAHR072B41S module.)

Job Name:			Location:		
Purchaser:			Order No.:		
Engineer:					
Submitted To:	For:	Ref:	Approval:	Construction:	
Submitted By:			Date:		
Unit Designation:			Schedule No.:		Model No.:

## FEATURES:

- Three-pipe system for ductless and ducted applications
- Inverter-driven scroll compressor
- Air source simultaneous cooling and heating with Change-Over Box
- Long refrigerant piping lengths – up to 3,280 feet total pipe run

## ACCESSORIES:

- Change-Over Box (required for a heat recovery system): for details see Change-Over Box Submittals
- Piping Kit: for details see Pipe Accessories Submittal
- Hail/Snow Protection Hood: for details see Snow/Hail Guards Kit Submittal

## NOTES:


- Rating Conditions are shown as below with piping length 24 feet 7-3/16 inch, piping height 0 feet.  
Cooling  
Indoor Air Inlet Temperature: 80 DB, 67F WB  
Outdoor Air Inlet Temperature: 95F DB  
Heating  
Indoor Air Inlet Temperature: 70 F DB  
Outdoor Air Inlet Temperature: 47F DB, 43F WB
- Rating Conditions are based on the AHRI 1230 test standard.
- For more details, please refer to Engineering manual "Operation range" section.
- For more details, please refer to Engineering manual "Operation range" section.
- External static pressure can be changed via DSW setting 0.24 in.W.G. (60Pa).

Category		Ton		14RT (8RT+6RT)	
Model (combination)				(H,Y)VAHR168B41S	
Model (individual)		Unit A		(H,Y)VAHR096B41S	
		Unit B		(H,Y)VAHR072B41S	
		Unit C		-	
		Unit D		-	
Power Supply				460V/ 3PH 60Hz	
Capacity (Nominal) <sup>1</sup>	Cooling	Capacity (Nominal)	Btu/h (kW)	168,000	(49.2)
		Power input	kW	13.69	
		Current input	A	19.1	
	Heating	Capacity (Nominal)	Btu/h (kW)	189,000	(55.4)
		Power input	kW	13.26	
		Current input	A	19.4	
Efficiency Ratings <sup>2</sup>	Cooling	Capacity (Rated)	Btu/h (kW)	160,000	(46.9)
		EER	Btu/Wh (W/W)	10.80	(3.17)
		IEER	Btu/Wh (Wh/Wh)	19.40	(5.69)
	Heating High	Capacity (Rated)	Btu/h (kW)	178,000	(52.2)
		COP	W/W	3.51	
	Heating Low	Capacity	Btu/h (kW)	129,000	(37.8)
		COP	W/W	2.16	
	Heat Recovery	SCHE	Btu/Wh	26.00	
Cooling Operating Range	Indoor	°F WB (°C WB)	59(15)~73(23)		
	Outdoor <sup>3</sup>	°F DB (°C DB)	14(-10)~118(48)		
Heating Operating Range	Indoor	°F DB (°C DB)	59(15)~80(27)		
	Outdoor <sup>4</sup>	°F WB (°C WB)	-4(-20)~59(15)		
Cabinet Color (Munsell Code)				2.5Y 8/2	
Outer Dimensions (H x W x D)		in		(68-1/8 x 37-7/8 x 31- 7/32) x 2	
Package Dimensions (H x W x D)		in		(74-1/4 x 40-5/8 x 34-1/32) x 2	
Weight	Net	lbs (kg)	1402	(636)	
	Gross	lbs (kg)	1506	(683)	
Connection Ratio		Total Indoor Unit Capacity		%	
		Max. (Recommendation) indoor units/system		-	
				39 (32)	
Heat Exchanger	Type			Multi-Pass Cross-Finned Tube	
	Material			Cu-Al (Anti-corrosion)	
Compressor	Type	Inverter		DA65PHD×2	
		Fixed Speed		DA65PHC×1	
	Motor Output (Pole)	kW (Pole)		4.8(6)+4.4(2)	
	Start Method			7.26(6)	
	Operation Range			inverter	
	Refrigeration Oil Type			9~100	
Crank Case Heater		W×Q'ty		FVC68D	
				40.8 (230V) ×6	
Fan	Type			Propeller Fan	
	Motor Output (Pole)	kW (Pole)		0.66(8)+0.49(8)	
	Quantity	Q'ty		2	
	Air Flow Rate	cfm (m <sup>3</sup> /min)		6884+6178 (195+175)	
	External static pressure <sup>5</sup>	in.WG (Pa)		0 (0)	
Electrical	Drive			Direct-drive	
	Min Circuit Amps	A		-	
	Recommended Fuse/Breaker Size	A		-	
	Maximum Fuse Size	A		-	
Sound Pressure Level	Cooling (Night-Shift)	dB(A)		65	(60)
	Heating	dB(A)		65	
Protection devices	Cycle			High pressure switch at 601psi (4.15MPa)	
	Inverter			Over-current protection	
	Compressor			Over-heat protection	
	PCB			Over-current protection	
Refrigerant	Type			R410A	
	Charge amount	lbs (kg)	18.7+16.1	(8.5+7.3)	
Refrigeration Oil	Charge amount	gal/Unit (l/Unit)	2.1+1.6	(7.9+6.0)	
Defrost Method				Reversed Refrigerant cycle	
Main Refrigerant Piping (Heat Recovery)	Low Pressure Gas Line	in (mm)	1-3/8	(34.93)	
	High/Low Pressure Gas Line	in (mm)	1-1/8	(28.58)	
	Liquid Line	in (mm)	3/4	(19.05)	

version 201611

## System Dimensions

Heat Recovery Type Model:  
(H,Y)VAHR168B41S



### NOTES:


1. Make sure that the outdoor unit A is placed on the indoor unit side.  
Arrange the outdoor units according to the capacity, A&R.
2. Check "Installation Manual" for the piping connection kit and piping connection size.
3. This drawing shows that there is 7/8 inch [22mm] clearance between the base units.  
In case of the outdoor unit with "Snow Protection Hood (Optional Parts)" or "Air Outlet Duct (Field-Supplied)", the clearance between the base units of more than 1-31/32 inch [50mm] is required.
4. The dimensions marked with  $\Phi$  indicates the mounting pitch dimension for anchor bolts.
5. The width of outer dimension and anchor bolt mounting position are changed by clearance between the base units.

Outdoor Unit Model	Combination of Base Unit Models	
	OUTDOOR UNIT A	OUTDOOR UNIT B
(H, Y) VAHR168B31S	(H, Y) VAHR096B31S	(H, Y) VAHR072B31S
(H, Y) VAHR168B41S	(H, Y) VAHR096B41S	(H, Y) VAHR072B41S

version 201611

# Piping Connection Dimensions

Unit: inch (mm)



Model Type	Field Piping (*)					A	B	C	D	E	F	G
	Heat Recovery System		Heat Pump System		Liquid							
	Low Pressure Gas	High/ Low Pressure Gas	Low Pressure Gas	High/ Low Pressure Gas								
72	1-1/8 (28.58)	7/8 (22.2)	-	1-1/8 (28.58)	1/2 (12.7)	7/8 (22.2)	7/8 (22.2)	3/8 (9.52)	5-29/32 (150)	5-29/32 (150)	13-3/8 (340)	8-1/16 (205)
96	1-1/8 (28.58)	7/8 (22.2)	-	1-1/8 (28.58)	1/2 (12.7)	1 (25.4)	1 (25.4)	1/2 (12.7)	6-11/16 (170)	6-11/16 (170)	12-25/32 (325)	7-7/8 (200)
120	1-1/8 (28.58)	7/8 (22.2)	-	1-1/8 (28.58)	1/2 (12.7)	1 (25.4)	1 (25.4)	1/2 (12.7)	6-11/16 (170)	6-11/16 (170)	12-25/32 (325)	7-7/8 (200)

\*Using the accessory pipe (refer to Table 3.6 "Factory-Supplied Accessories"), combine the piping size.

Figure 6.2 Refrigerant Piping Connection

version 201611

