

# VRF SYSTEMS PRODUCT LINE

## YORK® VRF Indoor Units





YORK VRF indoor units operate quietly and are easy to install, service and maintain.

A wide variety of non-ducted and ducted indoor units are available in styles and capacities to fit multiple applications. Units operate quietly with sound ratings

as low as 24.5 dBA. All indoor units are compatible with both air source and water source VRF units and associated controllers, adapters, and gateways.

Tons		0.5	0.7	1.0	1.3	1.5	2.0	2.3	2.5	3.0	4.0	4.5	5.0	6.0	8.0		
1-Way Cassette Indoor Unit		■															
2-Way Cassette Indoor Unit						■											
4-Way Mini Cassette Indoor Unit		■															
4-Way Cassette Indoor Unit		■							■								
Ceiling Suspended Indoor Unit					■		■		■								
Wall Mount Indoor Unit		■							■								
Floor Exposed Indoor Unit		■															
Floor Concealed Indoor Unit		■															
Ducted High Static Indoor Unit					■										■		
Ducted Medium Static Indoor Unit		■															
Ducted Slim Indoor Unit		■															
Multi-Position Air Handler Unit						■			■				■				
Dedicated Outside Air System (DOAS)																■	
EconoFresh Economizer Indoor Unit									■								

## Change-Over Boxes for Heat Recovery Systems

Single-Port Change-Over Box		4 Port Change-Over Box		8 Port Change-Over Box		12 Port Change-Over Box	
-----------------------------	---	------------------------	---	------------------------	--	-------------------------	---

# VRF SYSTEMS PRODUCT LINE

## Air Source VRF Outdoor Units

Heat Pump and Heat Recovery units offer an extended operating range: outdoor ambient temperature as low as -10°F in cooling mode and as low

as -13°F in heating mode. Mini VRF unit can operate in cooling mode down to 23°F and in heating mode down to -4°F outdoor temperature.

Low Ambient Heat Pump systems can provide high capacity heating down to -13°F outdoor temperature.

Tons		3	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	
Heat Recovery 208/230V & 460V					[Blue bar indicating compatibility from 6 to 36 tons]																
Heat Pump 208/230V & 460V					[Blue bar indicating compatibility from 6 to 36 tons]																
Low Ambient Heat Pump 208/230V & 460V					[Blue bar]			[Blue bar]						[Blue bar]							
Mini VRF Single- Phase Heat Pump 208/230V*		[Blue bar]																			

\*Mini VRF systems compatible with indoor units up to and including 5 tons.

## Water Source VRF Units

Unified heat pump/heat recovery units are compact and flexible and are compatible

with all indoor units, controllers, adapters, and gateways.

Tons		6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48
Water Source VRF Heat Pump/Heat Recovery 208/230V & 460V		[Blue bar]										[Dashed blue bar]											

Multi-module systems up to 48 tons available mid-2019.

## Controllers

Simplified Wired Controller (CIS01)	Wired Controller (CIW01)	Wireless Controller (CIR01)	Mini Central Controller (CCM01)	Large Central Controller (CCL01)	VRF Central Touchscreen Controller (CCXL01)

## Adapters and Gateways for Integration with BAS

LonWorks® Adapter (CLW01)	VRF Smart Gateway (CBN02)	VRF Cloud Gateway (CMNETS)

[www.york.com/vrf](http://www.york.com/vrf)

Johnson Controls, the Johnson Controls logo and YORK® are registered trademarks of Johnson Controls, Inc., or its affiliates, in the United States of America and/or other countries.

©2019 Johnson Controls, Inc. P.O. Box 423, Milwaukee, WI 53201 | Printed in the USA | PUBL-9066 | FEB 2019  
www.johnsoncontrols.com